




ELECTRICAL CHARACTERISTICS:

CONTACT CURRENT RATING: 1 AMPERES.

DIELECTRIC WITHSTANDING VOLTAGE: AC 500V R.M.S

INSULATION RESISTANCE: 500 MEGOHMS MINIMUM AT DC 500V.

CONTACT RESISTANCE: 30 MILLIOHMS MAXIMUM.

OPERATING TEMPERATURE: -55C TO 105C.

MECHANICAL CHARACTERISTICS:

CONTACT INSERTION FORCE: KG MAXIMUM.

CONTACT SEPARATION FORCE: KG MINIMUM.

MATERIALS:

CONTACT: BRASS..



INSULATOR: P.B.T. UL 94-V0 RATED.

SHELL: COLD ROLLED STEEL.

FINISHES:

CONTACTS:GOLD FLASHED.

SHELL:NICKEL,TIN,ZINC PLATED.

A	前鉚型(不通孔)	B	後鉚型 (通孔)
			

PART NO.	A±0.25	B±0.25	C±0.25	D±0.25	E±0.25	F±0.25
DS-O9S	30.80	25.00	16.30	7.90	12.60	5.90
DS-15S	39.20	33.32	24.70	7.90	12.60	5.90
DS-25S	53.05	47.04	38.40	7.90	12.60	5.90
DS-37S	69.40	63.50	54.80	7.90	12.60	5.90

力壯實業有限公司					
PART NAME		D-SUB FEMALE SOLDER TYPE			
DWG.NO	HC-035	SCALE	1:1	DATE	2001.03.05
CHECK		UNIT	mm	NAME	